

DESCRIPTION: Sport-Kote is an economical, durable, easy to apply, acrylic coating for use on exterior concrete and asphalt surfaces. It provides a non-skid finish on concrete stairs, walkways, and on tennis, handball and basketball courts. Sport-Kote can also be used on wood and metal surfaces. It is available in several standard colors and is also available in custom colors with a minimum order.

CAN BE USED ON:

- Concrete Surfaces
- Asphalt Surfaces
- Wood Surfaces
- Sidewalks
- Stairs
- And other Exterior Surfaces

PREPARATION: All surfaces must be dry and free of dust, dirt, oil, loose granules, gravel or peeling paint and all other foreign matter. Repair cracks and level low areas. Treat mildew, then rinse thoroughly, and allow to dry. Acid etch concrete that is especially smooth, dense or treated with a hardening compound. Neutralize acid and thoroughly rinse. Pressure wash entire surface for best results and allow to thoroughly dry. New concrete should age 30 days before applying Sport-Kote. New asphalt surfaces should cure a minimum of ten (10) days before application.

FOR BEST RESULTS: SURFACE TEMPERATURE MUST BE MINIMUM OF 55° F AND RISING. DO NOT APPLY LATE IN THE DAY OR IF HEAVY DEW OR RAIN IS EXPECTED WITHIN 12 HOURS. DO NOT INSTALL ON ANY SURFACE THAT HAS A WATERPROOF MEMBRANE OR NON-VENTED METAL DECK BELOW THE SURFACE. YEARLY INSPECTION AND MAINTENANCE WILL GREATLY ENHANCE THE LIFE OF THE COATING.

APPLICATION & COVERAGE RATE: Sport-Kote is to be applied in two coats by brush, roller or spray. **FOR CONCRETE SURFACES** mix 5 parts of Sport-Kote to 1 part of water and apply as a primer at the rate of 300 sq. ft. per gallon per coat. When properly cured, apply a second coat of Sport-Kote at a rate of 100 sq. ft./ gal. DO NOT dilute finish coat. **FOR ASPHALT SURFACES** apply 2 coats, each at 80 to 100 sq. ft. per gallon. Apply second coat perpendicular to first coat. Be certain first coat is fully dry before applying second coat. DO NOT dilute either coat. KEEP VEHICLE TRAFFIC OFF SPORT-KOTE FOR 72 HOURS.

CLEAN-UP: Clean tools with soap and water.

PRECAUTIONS: DO NOT allow stored product to freeze. Protective clothing and eyewear should be used during application. When transporting this product make certain that the pail is upright, the lid is tight, and pail is secure. Do not store at temperatures above 100°F.

TECHNICAL SPECIFICATIONS

Generic type:	Acrylic
Sheen:	Low
Solids by volume:	48%
Solids by weight:	52%
Weight per gallon:	11.4 lbs
Type of cure:	Coalescence
Film thickness:	16 mil wet; 7.68 mils dry
Viscosity:	95 KU
Reduction solvent:	Water
Flash point:	N/A
VOC:	22 lbs/gal; 26 grams/ltr
Elongation:	N/A

CHEMICAL CONSTITUENT PERCENTAGES:

Pigment		39.0%
	Titanium Dioxide	33.0%
	Calcium Carbonate	45.0%
	Silica Sand	22.0%
Vehicle		61.0%
	Acrylic Resin	20.0%
	Water	79.0%
	Ethylene Glycol	1.0%

CAUTION! HARMFUL IF SWALLOWED. MAY CAUSE EYE, SKIN AND RESPIRATORY IRRITATION. USE WITH ADEQUATE VENTILATION. KEEP CLOSED WHEN NOT IN USE. KEEP OUT OF REACH OF CHILDREN.

NOTICE: We warrant material to be free of defects at time of manufacture. Since we have no control over application or conditions, our only obligation shall be to replace any material shown to be defective at time of delivery. Labor to install the material is not included. We assume no liability for damage of any kind, including incidental or consequential damage, and the user accepts the product "as is." The suitability of the product for an intended use shall be solely up to the user. NO OTHER WARRANTY, EITHER EXPRESS OR IMPLIED, IS OFFERED AND NO PERSON MAY OFFER A WARRANTY FOR THIS PRODUCT THAT IS DIFFERENT FROM WHAT IS STATED HERE.

Warning! If you scrape, sand or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH-approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead.

Volatile Organic Compounds: Less than 250 grams/liter